



ESPLANADE



Technical Specifications

Weight	472 g/m2
Width	140 cm
Pilling ASTM D3512	4
Abrasion/martindale	100 000
Cleaning Code	W
Direction	RR
Repeat	N/A
Seam Slippage	144 lbs Warp
ASTM D 4034	198 lbs Filling
Tensile Strength	357 lbs Warp
ASTM D 5034	119 lbs Filling
Backing	NON Woven Backing
Composition	93% Polyester 4% Nylon 3% Cotton

Applications & Features



Flammability Norms

CALIFORNIA TB 117-2013 - NFPA 260 CLASS 1

Clean and Care

- Frequent wash may affect the performance of the product.
- Any stain, spills or soiling should be cleaned up promptly with a neutral soap solution using a cloth in smooth circular movements.
- We do not accept responsibility for any damage resulting from inappropriate use, chemical cleaning or additional impregnation.

The analytical results are referred only to the sample tested. Discoloration and colour deviations tolerated by permissible industrial standards do not constitute reasons for claims. Colour migration may occur. Pilling is a natural phenomenon that occurs due to daily use and frequent washing and cannot be avoided. We reserve the right to modify, at any moment and without notice, any product specifications.



WASH



BLEACH



DRY



IRON



DRYCLEAN

