




SUEDE

13 Colors



Technical Specifications

Roll Width	140 cm (+/-3%)
Roll Length (average)	40 / 50 m
Surface Composition	100% Polyester
Backing Composition	100% Polyester
Weight	714 g/lm (+/-5%)
Tensile Strength EN ISO 13934-1	Warp 960 N Weft 2400 N
Tear Growth Resistance EN ISO 13937-3	Warp 53 N Weft 80 N
Seam Slippage Resistance EN ISO 13936-2	Warp 1,0 mm Weft 1,0 mm
Abrasion Test EN ISO 12947-1,2	> 20.000
Pilling EN ISO 12945-2	4
Colour Fastness to Rubbing EN ISO 105-X12	Dry 4-5 Wet 4-5
Colour Fastness to Artificial Light EN ISO 105-B02	4-5
Snagging Test (Rotating Chamber) BS 8479:2008	4-5

Applications & Features



Liquid Repellent · Anti-Stain



Fire Proof Norms

BS 5852 Part 1 – Cigarette Test – PASS · EN 1021-1 – Cigarette Test – PASS · CA Tech. Bull. 117:2013 / NFPA 260 – Cigarette Test – PASS

Optional Treatments (back coating)

BS 5852 Source 0&1 / Crib5 / 1.1M / IMO PART 8

Each production requires prior validation to the applicable standard.

The flame-retardant performance is dependent on the foam used.



REACH Compliant · Respects the Environment

Respects the environment through application of new technologies in the production process



OEKO-TEX Standard 100

9342CIT CITEVE

Clean and Care

- Frequent wash may affect the performance of the product.
- Any stain, spills or soiling should be cleaned up promptly with a neutral soap solution using a cloth in smooth circular movements.
- We do not accept responsibility for any damage resulting from inappropriate use, chemical cleaning or additional impregnation.

The analytical results are referred only to the sample tested. Discoloration and colour deviations tolerated by permissible industrial standards do not constitute reasons for claims. Colour migration may occur. Pilling is a natural phenomenon that occurs due to daily use and frequent washing and cannot be avoided. We reserve the right to modify, at any moment and without notice, any product specifications.



WASH



BLEACH



DRY



IRON



DRYCLEAN



LEBANON
WILLIAM FARHAT CORPORATION
Farhat Bldg, Ground floor,
Blvd. Pr Michel El Murr,
Zalka, Amaret Chalhoub, Beirut
+961 3 679 922 sales@wilfar.com

SAUDI ARABIA
شركة وليم فرحات للديكور
CR# 1009143680
Tamouh Bldg 3rd floor Office 23, Prince Saoud Bin
Abdullah Bin Alwi Street, Al-Quirawan, Riyadh
+966 54 513 3783 sales@wilfar.com

UNITED ARAB EMIRATES
WILFAR L.L.C - FZ
CR# 104551047400001
Meydan Grandstand, 6th floor, Meydan Road,
Nad Al Sheba, Dubai
+971 56 743 5644 sales@wilfar.com