



SUETEX PVC



26 Colors



Technical Specifications

Roll Width	140 cm (+/-3%)
Roll Length (average)	20 m
Surface Composition	100% PVC
Backing Composition	100% Polyester
Weight	1050 g/lm (+/-5%)
Thickness	1,00 mm (+/-5%)
Tensile Strength EN ISO 1421	Warp 448 N 95% Weft 334 N 157,1%
Tear Growth Resistance EN ISO 4674-1	Warp 67,5 N Weft 73,2 N
Seam Slippage Resistance EN ISO 13936-2	Warp 1,5 mm Weft 1,5 mm
Abrasion Test EN ISO 5470-2	> 800.000
Permanent Creasing Behavior (Bally Test) DIN EN ISO 32100 / DIN 53359 – 200.000 cycles	PASS
Colour Fastness to Rubbing EN ISO 105-X12	Dry 5 Wet 5
Colour Fastness to Artificial Light EN ISO 105-B02 (Exposure Level 7)	> 7
Colour Fastness to Sea Water EN ISO 105-E02	5
Colour Fastness to Chlorine Water EN ISO 105-E03	5
Colour Fastness to Artificial Weathering EN ISO 105-B04	> 5
Resistance to Urine (Urea Solution)	PASS
Resistance to Hospital-Grade Disinfectant Cleaner	PASS
Anti-Static	PASS
Snagging Test (Rotating Chamber) BS 8479:2008 (2000 Turns)	4

Applications & Features

	Durability Performance Abrasion Test: > 800.000 cycles (Heavy Use)
	UV and Fade Resistance QUV 1000h
	IMO RES MSC.307(88) Part 8
	Resistance to Hydrolysis (10 years)
	Impermeability
	Resistance to Cold Cracking (-23°C)
	Chemical Solvents-Free
	Anti-Bacterial · Anti-Mildew
	Pet Friendly Scratch Resistance
	Fire Proof Norms BS 5852 Part 1 – Cigarette & Match – PASS · EN 1021-1/2 – Cigarette & Match – PASS · CA Tech. Bull. 117:2013 / NFPA 260 – Cigarette Test · FMVSS 302 – PASS
	REACH Compliant · Respects the Environment

Clean and Care

- To remove dust, use a vacuum cleaner.
- Any stain, spills or soiling should be cleaned up promptly with a neutral soap solution using a cloth in smooth circular movements; wipe dry.
- We do not accept responsibility for any damage resulting from inappropriate use, chemical cleaning or additional impregnation.

The analytical results are referred only to the sample tested. Discoloration and colour deviations tolerated by permissible industrial standards do not constitute reasons for claims. Colour migration may occur. We reserve the right to modify, at any moment and without notice, any product specifications.



WIPE



BLEACH



DRY



IRON



DRYCLEAN



LEBANON
WILLIAM FARHAT CORPORATION
Farhat Bldg, Ground floor,
Blvd. Pr Michel El Murr,
Zalka, Amaret Chalhouh, Beirut
+961 3 679 922 sales@wilfar.com

SAUDI ARABIA
شركة وليم فرحات للديكور
CR# 1009143680
Tamouh Bldg 3rd floor Office 23, Prince Saoud Bin
Abdullah Bin Alwi Street, Al-Quirawan, Riyadh
+966 54 513 3783 sales@wilfar.com

UNITED ARAB EMIRATES
WILFAR L.L.C - FZ
CR# 104551047400001
Meydan Grandstand, 6th floor, Meydan Road,
Nad Al Sheba, Dubai
+971 56 743 5644 sales@wilfar.com